

# ASPV600

The fast and compact solution to unwind spools. No forklift needed

La soluzione veloce e compatta per lo svolgimento delle bobine. Non richiede mezzi meccanici per il caricamento

La solución rápida y compacta para desenrollar las bobinas. No requiere medios mecánicos para la carga

AVAILABLE MODELS	ASPV600-V1	ASPV600-V2
Features Caratteristiche Características	<ul style="list-style-type: none"> <li>• For thin wire</li> <li>• Unwinding at high speed</li> </ul>	<ul style="list-style-type: none"> <li>• For medium wire</li> </ul>
Capacity Capacità di carico Capacidad de carga	450 Kg (992 lb)	
Spool diameter Diametro della bobina Diámetro de la bobina	ø 350 ÷ 780 mm (ø 13.7 ÷ 30.7")	
Max spool width Larghezza max bobina Ancho máxima bobina	400 mm (15.7")	
Recommended for wire Raccomandato per filo Recomendado para hilo	ø 0,2 ÷ 0,6 mm (ø .007 ÷ .02")	ø 0,35 ÷ 1,6 mm (ø .013 ÷ .06")
Max speed Velocità max Velocidad máxima	90 rpm	
Spool loading Caricamento bobina Carga de la carrete	Manual on rack	

