

ASC250/600-G3

Compact pay-off for 250 e 600 kg spools and bundles with safety perimeter guards

Kompakte Haspeln für Bündel und Spulen von 250 und 600 kg mit Schutzumwehrung

Dévidoirs compacts pour les bobines et les couronnes de 250 et 600 kg avec barrières de sécurité

AVAILABLE MODELS	ASC250-08-G3	ASC600-08-G3
Features Caratteristiche Características	- Reduced dimensions - It is not possible to install the double wire option and the shock absorber	
Capacity Capacità di carico Capacidad de carga	250 kg (551 lb)	600 kg (1322 lb)
Recommended for wire Raccomandato per filo Recomendado para hilo	$\phi 0,5 \div 3 \text{ mm}$ $(\phi .01 \div .11")$	
ϕ Plate ϕ Piatto ϕ Plato	$\phi 800 \text{ mm (31.5")}$ with or without 15 mm border	$\phi 800 \text{ mm (31.5")}$ with 40 mm border
Inside bundle diameter ϕ interno matassa ϕ interior madeja	$\phi 215 \div 600 \text{ mm}$ ($\phi 8.46 \div 23.6"$)	$\phi 215 \div 600 \text{ mm}$ ($\phi 8.46 \div 23.6"$)
Max speed Velocità max Velocidad máxima	85 rpm	
Guards features Caratteristiche barriere Características barreras	- Fixing to the ground is not mandatory, but is necessary if there is a risk of pay-off dragging in case of large wires, heavy spools or tangling at high speeds. - Double opening door	

