

ASC1000

Pay-off with lower plate for 1000 kg spools and bundles, with safety perimeter guards

Aspo con piano ribassato per bobine e rocchetti da 1000 kg, con barriere di protezione

Desbobinadores con placa inferior para bobinas y madejas de 1000 kg, con barreras de protección

AVAILABLE MODELS	ASC1000-14-G1	ASC1000-14-G2
Features Caratteristiche Características	• Double wire and shock absorber options available	
Capacity Capacità di carico Capacidad de carga	1000 kg (2204 lb)	
Recommended for wire Raccomandato per filo Recomendado para hilo	ø 0,5 ÷ 3 mm (ø .01 ÷ .11")	ø 1 ÷ 10 mm (ø .03 ÷ .39")
ø Plate ø Piatto ø Plato	1400 mm (55.1") With 40 mm border	
Height of the table Altezza del piatto Alto de la mesa	420 mm - 870 mm with ASC-OP-08 (16.5" - 34.2")	
Inside bundle diameter ø interno matassa ø interior madeja	ø 300 ÷ 1200 mm (ø 11.8 ÷ 47.2")	
Max Speed Höchstgeschwindigkeit Vitesse maximale	80 rpm	
Guards features Barrieren: Merkmale Caract. barrières	• Fixing to the ground is mandatory for just 3 poles • Double opening door	

