

Full automatic camera profile projectors

Proiettori di profili a telecamera automatici

Proyectores de perfiles automáticos con videocámara

LED2D FEATURES

- Extremely fast automatic measurements in fractions of a second
- Profile export function in CAD / DXF format
- Extremely easy to use
- Ideal for inspection of large quantities of parts
- Integrated with PMAR statistical and process control software
- Accessories and functions for measuring springs and small and large parts up to 500 x 250 mm
- Misurazioni automatiche velocissime, in frazioni di secondo
- Funzione Export del profilo in formato CAD / DXF
- Facilità estrema nell'uso
- Ideale per controllo di molti pezzi
- Integrato con software PMAR di statistica e controllo processo
- Accessori e funzionalità per la misura di molle e parti piccole e non fino a 500 x 250 mm
- Mediciones automáticas extremadamente rápidas, en fracciones de segundo
- Función de exportación del perfil en formato CAD / DXF
- Extrema facilidad de uso
- Ideal para el control de grandes cantidades de piezas
- Integrado con el software PMAR de estadística y control de procesos
- Accesorios y funciones para la medición de muelles y piezas pequeñas y grandes hasta 500 x 250 mm

AVAILABLE MODELS	LED2D-65	LED2D-100	LED2D-140	LED2D-M2
Field of view Campo di misura Campo de medida	63 x 45 mm (2.48 x 1.77")	106 x 75 mm (4.17 x 2.95")	142 x 100 mm (5.6 x 3.95")	500 x 250 mm (19.6 x 9.8")
*Accuracy *Accuratezza *Precisión	0,008 mm + 0,05% (.0004")	0,01 mm + 0,05% (.0004")	0,01 mm + 0,05% (.0004")	0,01 mm + 0,05% (.001")
Min measurable thickness Spessore min misurabile Espesor mín medible	0,05 mm (.002")	0,1 mm (.004")	0,15 mm (.006")	0,1 mm (.004")
Dimensions Ingombro Tamaño	200 x 400 x 720 mm (7.9 x 15.7 x 28.3")	225 x 430 x 890 mm (8.8 x 16.9 x 35")	1100 x 600 x 1680 mm (43.3 x 23.6 x 66")	800 x 785 x 850 mm (31.5 x 30.9 x 33.5")

*By using sharp and straight parts *Usando parti nitide e rettilinee *Usando partes nítidas y rectilíneas



LED2D-65 / LED2D-100



LED2D-140



LED2D-M2



OPTIONAL 2D-OP-01

Magnetic support in which the extension spring is housed, allowing it to be rotated so as to ensure correct positioning and measurement between the eyelets

Supporto magnetico in cui alloggia la molla a trazione permettendo di ruotarla così da garantire un corretto posizionamento e la misura tra gli occhielli

Soporte magnético en el que se aloja el muelle tensor, que permite girarlo para asegurar un correcto posicionamiento y medida entre los ojales

